



FL-1950-1D 50w Led floodlight IP65



colour	ww-nw-cw
colour temperature	3000/4500/6500K
power factor	>0.95
voltage	200-240V
efficacy l/w	70-80 lm/w
led type	SMD5730
dimnable	yes
total lumen	3500-4000
life time	50.000 hrs
cri	80
beam angle	120 deg
wattage	50 watt
replacement for	200 watt
size	290x290x70 mm
lamp material	Aluminum + glass
certificates	ce/rohs / SAA
ip grade	IP65
warranty	2 years

Note

Specifications listed are in effect at time of printing and are subject to alteration without prior notice or obligation. RAW LED reserves the right to periodically upgrade these specifications through additions, deletions and substitutions.

RAW LED B.V.





Hellingweg 134 | 2583 DX The Hague | The Netherlands

T +31(0)70 322 54 73 | F +31(0)70 358 41 80 | info@rawled.com | www.rawled.com



raw *led*

Light output (spectral distribution)



UNIT: cd

- C0/180, 121.1 deg
- C30/210, 122 deg
- C60/240, 122.1 deg
- C90/270, 121.7 deg

AVERAGE BEAM ANGLE (50%): 121.8DEG



raw ^{led}

Packaging details

Carton size	595*375*320MM
Pieces	10
Gross Weight	20.5kg